



# JS 80 R

Removable security bollard

TYPE OF OPERATOR

Removable

HEIGHT

1,000 mm



JS 80 R



JS 80 R INOX

- Removable cylinder to allow temporary access
- Interchangeable protective sleeve so that the bollard is always just like new.
- Performance certified according to PAS 68; IWA 14-1 and ASTM F2656 standards. Able to withstand impact with a truck driven at 80 km/h. P1 penetration rating
- "Shallow Mounted" design: minimum hole depth required



# JS 80 R

# FAAC

Removable security bollard

## TECHNICAL SPECIFICATIONS

Model	JS 80 R	JS 80 R INOX
Cylinder height from ground	1,000 mm	
Cylinder diameter	275 mm	
Cylinder treatment	Cataphoresis	
Protective sleeve type	mDure®	Aisi 316 stainless steel + mDure®
Reflective strip height	55 mm	
Standard reflecting strip colour	White	
Head material type	Aluminum	
Head treatment type	Rilsan® anticorrosive resin	
Weight of underground base	120 kg	
Type of use	Perimeter Security	
Break in resistance	1.852.000 J	
Traffic bollard weight	320 kg	

CE

[www.faactechnologies.com](http://www.faactechnologies.com)

FAAC S.p.A - Soc. Unipersonale - Via Calari 10 - 400069 Zola Predosa (BO) Tel. +39 051 61724